

NeuroElf pipeline

ne_fmriquality.m

modification of original fmriquality with options for outliers analysis IK 2014

does not work with NE v1.0 (many @neuroelf\private function that are used inside are missing)

<http://neuroelf.net/wiki/doku.php?id=fmriquality> : **Finally, at the moment, the “problem detection” thresholds (to mark a volume as outliers) are fixed, but are likely to change in a future version.**

Create VTC

http://neuroelf.net/wiki/doku.php?id=vmr.createvtc#method_reference_vmrhelp_createvtc

Current issue that it doesn't work with monkey data - sag, cor and axi planes are confused in the resulting VTC.

Sources\MATLAB\bv_umg\ne_era

ne_era.m

This function relies on vtc.VOITimeCourse method, which has been changed from v0.9c → newer versions. The new method is AFT::VOITimeCourse, in versions v0.9d and 1.0, this method works only with TAL vois. The method vtc.VOITimeCourseOrig is kept for backward compatibility (works with both BV and TAL vois).

ne_era.m takes care of this:

```
if strcmp('0.9c',v) || strcmp(voi.ReferenceSpace,'TAL'),  
    tc = vtc.VOITimeCourse(voi)'; % each row - one roi tc  
else  
    tc = vtc.VOITimeCourseOrig(voi)';  
end
```

From:

<http://dag.dokuwiki.dpz.lokal/> - DAG wiki

Permanent link:

http://dag.dokuwiki.dpz.lokal/doku.php?id=neuroelf:neuroelf_pipeline&rev=1439674097

Last update: 2022/12/29 07:15

