

NeuroElf Resources

Online resources

<http://neuroelf.net/>

<http://neuroelf.net/wiki/doku.php>

<https://www.youtube.com/channel/UC1sM-zqnmdcZOrRf-i0FLGg> | NeuroElf youtube tutorials!

Help

For getting detailed help on each method of xff object (e.g. fmr), use:

```
>> fmr.Help % to see all methods
>> fmr.Help('Method') % e.g. fmr.Help('Realign') to see details of each method
```

See <http://neuroelf.net/wiki/doku.php?id=obj.help>

NeuroElf-based ERA

http://neuroelf.net/wiki/doku.php?id=neuroelf_gui_-_mdm_voi_condition_average_ui

<http://neuroelf.net/wiki/doku.php?id=mdm.voicondaverage>

DAG installation notes

1) During installation, disable (remove from path) Chronux: conflict with linec.m

2) NeuroElf functions use std.m and var.m as in newer versions of MATLAB, with 3 inputs: e.g. Y = STD(X,FLAG,DIM). Therefore, NaN toolbox functions std.m and var.m are incompatible, remove it from path. Revise sterr.m and corrcoef_eval.m and place to lgtools.

3) Starting from NeuroElf_v09d, many useful auxiliary scripts/functions are “hidden” behind @neuroelf method, and reside in **..\@neuroelf\private**. They can be placed in the path (i.e. copied to the main NeuroElf folder, it is not possible to add to path this private folder directly), or accessed as described in [main installation folder] / README.html > Function library:

```
>> netools = neuroelf;
>> list_of_files = netools.findfiles(startfolder, pattern);
```

Currently required functions for DAG NeuroElf-based functions (\Sources\MATLAB\bv_umg):

- findfiles
- checkstruct
- renamefile
- dicom_dic

Used by ne_pl_fmriqasheet.m:

- psctrans
- packmosaic
- scaledata
- minmaxmean
- splittocell

4) There is a bug in NeuroElf v1.0 and v0.9d, to fix please replace the function dcm_Value.m in /xff/private with the function below. This function is used by createfmr.m

[dcm_Value.m](#)

```
function dcmval = dcm_Value(hfile, vkey, varargin)
% DCM::Value - return a tag's value
%
% FORMAT:      dcmval = dcm.Value(key [, ...]);
%
% Input fields:
%
%      key      DICOM key (0008.0010) or tag (PatientsName)
%      ...      default value if not found
%
% Output fields:
%
%      dcmval    value for given key/tag
%
% Using: makelabel, splittocell.

% Version:  v0.9d
% Build:    14082218
% Date:     Aug-22 2014, 6:14 PM EST
% Author:   Jochen Weber, SCAN Unit, Columbia University, NYC, NY, USA
% URL/Info: http://neuroelf.net/
%
% Copyright (c) 2010, 2011, 2014, Jochen Weber
% All rights reserved.
%
% Redistribution and use in source and binary forms, with or without
% modification, are permitted provided that the following conditions
% are met:
%      * Redistributions of source code must retain the above copyright
%      notice, this list of conditions and the following disclaimer.
%      * Redistributions in binary form must reproduce the above
%      copyright
%      notice, this list of conditions and the following disclaimer in
```

```

the
%      documentation and/or other materials provided with the
distribution.
%      * Neither the name of Columbia University nor the
%      names of its contributors may be used to endorse or promote
products
%      derived from this software without specific prior written
permission.
%
% THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND
% ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED
% WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE
% DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDERS BE LIABLE FOR ANY
% DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES
% (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES;
% LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
CAUSED AND
% ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR
TORT
% (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS
% SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

% neuroelf library
global ne_methods;

% persistent dictionaries
persistent dcmv_dicts
if isempty(dcmv_dicts)
    dcmv_dicts = struct;

    % load standard dict
    dcmv_dicts.OFFIS = ne_methods.dicom_dic(); % IK added ne_methods
and ()

end

% only valid for single file
if nargin < 2 || ...
    numel(hfile) ~= 1 || ...
    ~xffisobject(hfile, true, 'dcm')
    error( ...
        'xff:BadArgument', ...
        'Invalid call to %s.', ...
        mfilename ...
    );

```

```
end

% dict
bc = xffgetcont(hfile.L);
dict = bc.DataDictionary;

% check key
if ischar(vkey)
    vkey = vkey(:)';
    if length(vkey) == 9 && ...
        ~isempty(regexp(vkey, '^([0-9a-f]{4})([0-9a-f]{4})$'))
        vkey = vkey([1:4,6:9]);
    end
    if length(vkey) == 8 && ...
        ~isempty(regexp(vkey, '^([0-9a-f]+)$')) && ...
        ~all(double(vkey) > 64)
        vkey = ['k_' upper(vkey(1:4)) '_' upper(vkey(5:8))];
    elseif ~strcmp(vkey, ne_methods.makelabel(vkey))
        error( ...
            'xff:BadArgument', ...
            'Invalid DICOM tag number/key given.' ...
        );
    else
        if isempty(dict)
            warning( ...
                'xff:InternalWarning', ...
                'Data dictionary not looked up.' ...
            );
            dcm_DetectDictionary(hfile, 'auto');
            dict = bc.DataDictionary;
        end
        if ~isfield(dcmv_dicts, dict)
            error( ...
                'xff:BadSetting', ...
                'Unknown DICOM dictionary set.' ...
            );
        end
        dict = dcmv_dicts.(dict);
        if ~isfield(dict, vkey)
            error( ...
                'xff:BadArgument', ...
                'Unknown DICOM tag key given.' ...
            );
        end
        vkey = dict.(vkey);
        if isfield(bc.DataKeyLookup, vkey)
            dcmval = bc.Data(bc.DataKeyLookup.(vkey)).Value;
        elseif isfield(bc.MetaKeyLookup, vkey)
            dcmval = bc.Meta(bc.MetaKeyLookup.(vkey)).Value;
        elseif nargin > 2
```

```

        dcmval = varargin{1};
    else
        error( ...
            'xff:BadArgument', ...
            'Given DICOM tag key not present in file.' ...
        );
    end
    dcmval = interpret_dcmval(dcmval);
    return;
end
if ~isfield(bc.DataKeyLookup, vkey)
    if nargin < 3
        error( ...
            'xff:BadArgument', ...
            'Given DICOM tag not present in file.' ...
        );
    else
        dcmval = varargin{1};
        dcmval = interpret_dcmval(dcmval);
        return;
    end
end
dcmval = bc.Data(bc.DataKeyLookup.(vkey)).Value;
dcmval = interpret_dcmval(dcmval);

% numeric key format
elseif isa(vkey, 'double')
    if numel(vkey) == 2 && ...
        ~any(isinf(vkey) | isnan(vkey) | vkey < 0 | vkey > 65535)
        try
            dcmval = dcm_Value(hfile, sprintf('%04x%04x', vkey(1),
vkey(2)), varargin{:});
        catch ne_eo;
            rethrow(ne_eo);
        end
    elseif numel(vkey) == 1 && ...
        nargin > 2 && ...
        isa(varargin{1}, 'double') && ...
        ~isinf(vkey) && ...
        ~isnan(vkey) && ...
        vkey >= 0 && ...
        vkey < 65536 && ...
        numel(varargin{1}) == 1 && ...
        ~isinf(varargin{1}) && ...
        ~isnan(varargin{1}) && ...
        varargin{1} >= 0 && ...
        varargin{1} < 65536
        try
            dcmval = dcm_Value(hfile, sprintf('%04x%04x', vkey,
varargin{1}), varargin{2:end});
        catch ne_eo;

```

```
        rethrow(ne_eo);
    end
else
    error( ...
        'xff:BadArgument', ...
        'Invalid DICOM tag (or key) given.' ...
    );
end
dcmval = interpret_dcmval(dcmval);

else
    error( ...
        'xff:BadArgument', ...
        'Invalid DICOM tag (or key) given.' ...
    );
end

% sub function
function dcmval = interpret_dcmval(dcmval)
    global ne_methods;
    if ischar(dcmval) && ...
        ~isempty(dcmval)
        dcmval = dcmval(:)';
        if ~isempty(regexpi(dcmval, ...
            '^s*[\+\-]?\d+(\.\d+)?([eE][\+\-]?\d+)?(s*\s*s*[\+\-]?\d+(\.\d+)?([eE][\+\-]?\d+)?)*s*$'))
            dcmvalc = ne_methods.splittocell(dcmval, '\');
            dcmvaln = zeros(1, numel(dcmvalc));
            try
                for vc = 1:numel(dcmvalc)
                    dcmvaln(vc) = str2double(dcmvalc{vc});
                end
            catch ne_eo;
                neuroelf_lasterr(ne_eo);
                return;
            end
            dcmval = dcmvaln;
        end
    elseif isnumeric(dcmval)
        dcmval = double(dcmval);
    end
end
% end of function dcmval = interpret_dcmval(dcmval)
```

From:

<http://dag.dokuwiki.dpz.lokal/> - **DAG wiki**

Permanent link:

http://dag.dokuwiki.dpz.lokal/doku.php?id=neuroelf:neuroelf_resources&rev=1439673406

Last update: **2022/12/29 07:15**

